

Packstat PS073 is primarily a foam compression sealant. The product is white. The foam is open celled and is a soft foam. An acrylic pressure sensitive adhesive is coated on one side, and the product has a fixed Polyester liner on the other non-adhesive face. PS073 will act as an air and dust seal when compressed.

PRODUCT BENEFITS

- Minimum 50% compression required to effect an air/dust seal.
- Service temperature: -30°C to +70°C.
- Application temperature: +10°C to +40°C.
 - Shelf life of 1 year from dispatch.
- Coated on one side with a high-quality pressure sensitive acrylic adhesive.
- Good resistance to dilute acids and alkalis
 - Very good ultraviolet {UV} light resistance
 - Resistance to abrasion, corrosion and moisture.
- Suitable for indoor and outdoor environments.
- No known hazards associated with this product.
- Pre-determined dimensional sealant reduces waste.

Main Applications

- Forms a compression air / dust seal.
- For preventing electrolytic corrosion.
- For cushioning.
- For gap filling.
- For make-or-break seals

Product Properties	Unit	Nominal Value
10 Minute 180°C Peel Adhesion	N/25mm	5
Force To Compress by 50%	N/cm ²	0.85
Compression Deflection After 1 Minute	N/cm ²	0.65
Foam Density	Kg/m ³	125