

**Packstat PS090** is a medium performance double-sided foam bonding tape. The product is white. The Polyethylene foam is predominantly closed celled. A high tack, acrylic, pressure sensitive adhesive is coated

on both sides. The product has a white, glassine, paper release liner. The material can also be supplied with a green filmic liner facilitating automated application.

#### PRODUCT BENEFIT

- Pre-determined dimensional sealant reduces waste.
- No known hazards associated with this product.
- Resistance to abrasion, corrosion and moisture.
- Very good ultraviolet {UV} light resistance.
- Paper release liner, reducing dimensional change during application.
- Good resistance to dilute acids and alkalis.
- Coated on both sides with a high-quality pressure sensitive acrylic adhesive.

#### Main Applications

- Aluminium spacer profile bonding to glass.
- Bonding of PVCu decorative trims.
- External vehicle mirror assembly bonding.
- Bonding plastic profiles (cable management)

Product Properties	Unit	Nominal Value
Thickness	mm	1
10 Minute 180° Peel Adhesion	N/25mm	21
500-hour Static Shear (Stainless Steel)	Kg/cm <sup>2</sup>	0.16
Dynamic Shear	N/cm <sup>2</sup>	45

28th December 2020

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.

Packstat Ltd, Ely Valley Business Park, Pontyclun, CF72 9DZ | T 01443 223361 | [enquiries@packstat.co.uk](mailto:enquiries@packstat.co.uk) | [packstat.co.uk](http://packstat.co.uk)