

Packstat PS248 is a high-performance double-sided tape based on a transparent polyester film carrier coated on both sides with flame retardant acrylic adhesive protected with 80g/m² amber silicone paper release liner. NMS24 adhesive is dark grey on the open side and black on the liner (closed) side.

PRODUCT BENEFITS

- Light weight and thin bonding solution.
- Remains flexible and allows the application on rough surfaces.
- Tape leaves no residue on the floor upon removal.
- Very high adhesion (closed side).
- Differential colours between both sides, with grey side to stick on the floor and black side to stick onto tape.
- Thin film carrier for a low total weight.
- Pass flammability requirements of FAR/JAR/CS 25.853 (a) APP. F Pt I(a)(1)(ii).

Main Applications

- Carpet and gallery mats fixing in the transport industry, when fire retardant properties are needed.

Product Properties	Unit	Nominal Value
Flame Resistance After Flame	Seconds	0
Flame Resistance Burn length	mm	83.8
Flame Resistance Drip Extinguishing Time	Seconds	0
Peel Adhesion on Steel Grey Open Side	N/cm	4.4
Peel Adhesion on Steel Black Liner Side	N/cm	16.0
Total Thickness	Microns	130
Total Weight	g/m ²	162
Roll Length	Meters	50
Core	mm	76