

Packstat PS027 reliably guarantees razor-sharp paint edges and is extremely easy to use at the same time - thanks to the ideal combination of the special, supple backing and the perfectly balanced acrylic adhesive compound. This helps the tape to stick extremely flush to the surface and prevent paint tears. The combination of professional painting tape and your skilled expertise will result in paintwork to please your customers. In addition, the high quality of the painting tape will save you expensive touch-up work. It is also recommended for masking applications during spray painting with afterwards oven drying up to 120°C/ 30min. Due to the thin and low elongating backing it is perfectly suited for two-tone applications, e.g. straight and long lines.

Product Benefits

- Indoor masking (up to 6 months)
- Outdoor masking (up to 8 weeks)
- For smooth and slightly textured
- Surfaces
- For high-quality painting and lacquering work
- For spray painting with afterwards oven
- Drying up to 120°C/30 min

Main Applications

- For use for razor-sharp edges while painting on masked areas

Product Properties	Unit	Nominal Value
Thickness	µm	90
Tensile Strength	N/cm	30
Adhesion to Steel	N/cm	1.8
Temperature resistance	°C	80
Elongation at break	%	4
Colour	N/A	Black

28th April 2026

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.

Packstat Ltd, Ely Valley Business Park, Pontyclun, CF72 9DZ | T 01443 223361 | enquiries@packstat.co.uk | packstat.co.uk