

Packstat PS073 is primarily a foam compression sealant. The product is white. The foam is open celled and is a soft foam. An acrylic pressure sensitive adhesive is coated on one side, and the product has a fixed Polyester liner on the other non-adhesive face. PS073 will act as an air and dust seal when compressed.

Product Benefits

- Minimum 50% compression required to affect an air/dust seal.
- Service temperature: -30°C to +70°C.
- Application temperature: +10°C to +40°C.
- Shelf life of 1 year from dispatch.
- Coated on one side with a high-quality pressure sensitive acrylic adhesive.
- Good resistance to dilute acids and alkalis
- Very good ultraviolet {UV} light resistance
- Resistance to abrasion, corrosion and moisture.
- Suitable for indoor and outdoor environments.
- No known hazards associated with this product.
- Pre-determined dimensional sealant reduces waste.
- Clean to use / clean edge finish.

Main Applications

- Forms a compression air / dust seal.
- For preventing electrolytic corrosion.
- For cushioning.
- For gap filling.
- For make-or-break seals

Product Properties	Unit	Nominal Value
10 Minute 180°C Peel Adhesion	N/25mm	5
Force To Compress by 50%	N/cm ²	0.85
Compression Deflection After 1 Minute	N/cm ²	0.65
Foam Density	Kg/m ³	125

Accreditation:

Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

Recommendations:

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.