

**Packstat PS281** is a black acrylic foam tape. It consists of a high-performance acrylic system and due to its unique components it combines a very good temperature resistance with an outstanding cold shock resistance up to -40°C. It is designed for demanding outdoor bonding applications especially in combination with an Adhesion Promoters. The visco-elastic, foamed acrylic core

**Product Benefits**

- Outstanding cold shock performance down to -40 °C
- In combination without adhesion promoters a secure and reliable bond in outdoor conditions

**Main Applications**

- Bonding of panels and reinforcement bars in the following Industries:
- Elevator
  - Transportation
  - Production equipment

**Certificates**

- PS281 is recognized according to UL Standard 746C. UL File QOQW2.E309290
- RST Fire testing in accordance with DIN EN 45545-2, EN ISO 5658-2
- Qualified for a credit according to LEED.

**Liner options**

PV24: Blue film liner - unbranded

Product Properties	Unit	Nominal Value
Backing		Foamed acrylic
Type of adhesive		Pure acrylic
Total thickness	µm	500
Colour		Black
Short Term temperature resistance	°C	220
Long Term temperature resistance	°C	120
Adhesion to ABS (initial)	N/cm	2
Adhesion to ABS (after 14 days)	N/cm	3
PP (initial)	N/cm	1
PP (after 14 days)	N/cm	1
Adhesion to Steel (initial)	N/cm	12
Adhesion to Steel (after 14days)	N/cm	27
Adhesion to Steel (after 3 days)	N/cm	27

28<sup>th</sup> April 2026

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.