

**Packstat PS319** is a high temperature resistant masking tape for up to 160°C.

### Product Benefits

- The natural rubber adhesive offers high tack and excellent adhesion on a variety of surfaces like metal, rubber, glass and plastic.
- The excellent adherence of fillers or paints (water- or solvent-based) to the reverse side of the tape prevents any kind of paint flaking, even after the oven-drying process with temperatures of up to 160 °C.
- It can be easily removed without leaving any residues.
- The conformable masking tape is resistant to wet sanding and can withstand high temperatures, making it suitable for oven-drying.

### Main Applications

- Suitable for temperatures up to 160°C - ideal for demanding automotive masking jobs during spray painting
- High adhesion on various surfaces (metal, rubber, glass, plastic) and holds masks securely
- Excellent paint anchorage on reverse side

| Product Properties              | Unit | Nominal Value         |
|---------------------------------|------|-----------------------|
| Adhesive Type                   | n/a  | natural rubber        |
| Backing material                | n/a  | slightly-creped paper |
| Total thickness                 | µm   | 170                   |
| Elongation at break             | %    | 12                    |
| Tensile strength                | N/cm | 47                    |
| Hand tearability                | n/a  | very good             |
| Temperature resistance (60 min) | °C   | 160                   |