

**Packstat PS343** is a precision masking tape developed for professional painting and finishing tasks on sensitive surfaces. The tape uses an ultra-thin yet tear-resistant Washi paper backing and an acrylic adhesive system that offers balanced adhesion.

### Product Benefits

- **Precision edge masking** – Ultra-thin Washi backing ensures sharp paint lines and minimal paint bleed.
- **Low-tack adhesion** – Optimized acrylic adhesive (0.6 N/cm) protects delicate surfaces.
- **Clean removability** – Residue-free removal for up to **14 days** after application.
- **Stable handling performance** – High tensile strength and controlled elongation for reliable masking.

### Main Applications

- Precision indoor masking for painting and decorating
- Masking of sensitive surfaces such as wallpaper, wall coverings, and varnished surfaces

Product Properties	Unit	Nominal Value
Elongation at break	%	4.5
Tensile strength	N/cm	41
Sharp colour edge	n/a	very good
Residue-free removable after...	n/a	14 days
Hand tearability	n/a	very good
Adhesion to Steel	N/cm	0.6

28<sup>th</sup> April 2026

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.

Packstat Ltd, Ely Valley Business Park, Pontyclun, CF72 9DZ | T 01443 223361 | [enquiries@packstat.co.uk](mailto:enquiries@packstat.co.uk) | [packstat.co.uk](http://packstat.co.uk)