

Packstat PS411 is a grey double-sided, visco-elastic acrylic foam tape. The visco-elastic acrylic foam core absorbs and dissipates dynamic and static loads. Due to this unique formulation, this double-sided acrylic foam tape can compensate for thermal elongations of bonded parts.

Product Benefits

- Superior grip strength
- Outdoor and indoor use
- Joining of similar and dissimilar surfaces
- Creates durable and lightweight seals
- Suitable for signage, decorative trim, emblems and sign channel fixing
- PFAS/PFOS free product

Main Applications

- Suitable for a wide range of multi-purpose bonding applications
- Suitable for bonding applications such as emblem, decorative part or signage mounting.

Additional Information

Please note that we recommend using tesa® Adhesion Promoter as a surface pre-treatment. It leads to a significant improvement in adhesion levels, avoids moisture infiltration, and promotes long-term resistance against harsh environmental factors. Which tesa® Adhesion Promoter should be used depends on the substrates and the application. We will be glad to advise you in order to find the right solution.

Product Properties	Unit	Nominal Value
Backing		Foamed acrylic
Type of adhesive		Pure acrylic
Total thickness	µm	800
Colour		Grey
Short term temperature resistance	°C	200
Long term temperature resistance	°C	100
Adhesion to ABS (initial)	N/cm	1
Adhesion to ABS (after 14 days)	N/cm	2
Adhesion to Aluminium (after 3 days)	N/cm	35
PP (initial)	N/cm	1
PP (after 14 days)	N/cm	1
Adhesion to Steel (initial)	N/cm	16
Adhesion to Steel (after 14days)	N/cm	28
Adhesion to Steel (after 3 days)	N/cm	28