

**Packstat P587** is a translucent, double-sided non-woven tape equipped with flame retardant tackified acrylic adhesive.

This tape has especially been developed for power battery demanding mounting, lamination and converting application with flame retardant property as added value. Due to its non-flammable property, it is particularly designed to meet power battery automobile requirement.

Adhesion to	Unit	Nominal Value
ASTM (initial)	N/cm	8.9
PET (initial)	N/cm	7.8
PI (initial)	N/cm	7.1

### Product Benefits

- Flame retardant per UL 94 VTM-0 level
- Good bonding performance
- High long-term reliability and aging resistance
- Conforming to RoHS, REACH
- Halogen-free

### Main Applications

- Mounting in power battery or lamination application required additional flame-retardant property.

30<sup>th</sup> April 2026

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.

Packstat Ltd, Ely Valley Business Park, Pontyclun, CF72 9DZ | T 01443 223361 | [enquiries@packstat.co.uk](mailto:enquiries@packstat.co.uk) | [packstat.co.uk](http://packstat.co.uk)